



ENERGY
EDO
 EDO777218

A
B
C
D
E
F
G

20
kWh/1000h

1620 lm
 4000K
 220-240 V AC
 50-60Hz
 110°
 IP65
 IK05

2019/2015

Floodlight DORAN LED 20 W

LED floodlights are a perfect replacement for traditional halogen bulbs to illuminate larger surfaces. DORAN is a simple series of floodlights, the task of which is to fulfill the tasks at a high level. An adjustable screen will allow you to freely choose a lit place, and thanks to a stable leg, it can be set up and moved from place to place.

SPECIFICATIONS	EDO777218
Source Type:	Floodlight LED
Application:	inside/outside
Installation:	surface
Adjustable:	yes
Dimensions [mm]:	
- height [mm]:	135mm
- width [mm]:	130mm
- depth [mm]:	60mm
Colour:	black
Material:	aluminium, glass
Cover colour:	transparent
Energy efficiency class [A-G]:	F
Cooperation with a dimmer:	no
Sensor:	-

TECHNICAL DATA	
Power in the on-mode P _{on} [W]:	20W
Standby power P _{sb} /P _{net} [W]:	-
Rated voltage [V]:	220-240 V AC
Rated frequency [Hz]:	50-60 Hz
Color temperature [K]:	4000 K
Light color change:	no
Lighting angle [°]:	110°
Color rendering index CRI:	≥70
Color rendering index R9:	14
Useful luminous flux [lm]:	1620 lm
Light distribution angle [°]:	wide cone (120°)
Luminous efficiency [lm/W]:	81 lm/W
Rated life [h]:	25000 h
Number of cycles on/off:	15000
On-mode energy consumption [kWh/1000h]:	20kWh/1000h
IP:	IP65
IK:	IK05
Klasa ochronności:	I
Mercury content:	no
Environmental conditions:	-20°C...40°C

LOGISTIC DATA	
Collective packaging [pc.]:	20pc.
Weight [g]:	266g
EAN:	

