



SPECIFICATIONS EDO777614

| | |
|--------------------------------|--------------------------------|
| Source type: | Ceiling lamp with built-in LED |
| Application: | indoor |
| Type of assembly: | surface-mounted |
| Installation site: | ceiling and wall |
| Connection type: | screw cube |
| Colour: | white cover with black frame |
| Material: | cover and lampshade- PCV |
| Dimensions [mm]: | |
| -width [mm]: | ø350mm |
| -length [mm]: | - |
| -height [mm]: | 55mm |
| Adjustable: | no |
| Lampshade: | mat |
| Replaceable light source: | no |
| Energy efficiency class [A-G]: | F |
| Cooperation with a dimmer: | no |

PERETI LED PRO Black 24W NW

| | |
|--|---------------|
| TECHNICAL DATA | |
| Power in the on-mode P_{on} [W]: | 24W |
| Standby power P_{sby}/P_{net} [W]: | / |
| Rated voltage [V]: | 220-240V |
| Rated frequency [Hz]: | 50 Hz |
| Color temperature [K]: | 4000K |
| Light color change: | no |
| Light distribution angle [°]: | 120° |
| Color rendering index CRI: | 80 |
| Color rendering index R9: | 13 |
| Total luminous flux [lm]: | - |
| Useful luminous flux [lm]: | 2400lm |
| Measurement of the luminous flux in [°]: | sphere (360°) |
| Luminous efficiency [lm/W]: | 100lm/W |
| Rated life [h]: | 25000h |
| Number of cycles on/off: | 15000 |
| On-mode energy consumption [kWh/1000h]: | 24kWh/1000h |
| IP: | IP44 |
| Protection class: | II |
| Mercury content: | no |
| Environmental conditions [°C]: | -20°C...40°C |

LOGISTIC DATA

| | |
|------------------------------|-------|
| Collective packaging [pcs.]: | 5pcs. |
| Weight [g]: | 616g |
| EAN: | |

